

Penguin Coil Wrapper wraps the coil shaped products through the eye of the product in a spiral manner. The wrapping material is applied over the product using stretch rollers supported on a vertical ring which has a provision of passing the coil through eye horizontally.

Salient Features

- Enables torus shaped products to be wrapped through eye
- **___** Same machine for a wide range of coils to be wrapped
- Suitable to use with stretch film roll and HDPE woven fabric
- Adjustable film overlap & cycle time

Specifications

DIMENSION OF COILS TO PACK

Inner diameter	: Max. 600mm; Min. 400mm
Outside diameter	: Max. 900mm; Min. 600mm
Height	: Max. 350mm; Min. 200mm
Weight	: Max. 150 kg
FILM DETAILS	
Material	:LLDPE; 12–15 microns thick
Filmwidth	:100mm
Core diameter	: 25.4 mm
Max. film diameter	:150 mm
No. of packing rolls	:2 (one for stretch film roll;
	one for HDPE Woven fabric)
MACHINE	

Table height	:960mm
Max. ring speed	:70 rpm
Power requirement	: 440V, Three phase , 50 Hz
Installed power	:3.0 kW/4.0HP

Manufactured by



Factory:

3 / 184, Kondayampalayam Vaiyampalayam Post Coimbatore - 641 110. Tamil Nadu INDIA Tel: +91 - 422 - 94436 77432 / 94436 77804

Office:

"The Rookery", 46-B, KRK Road Krishnasamy Nagar II Layout Ramanathapuram Coimbatore - 641 045. Tamil Nadu INDIA Tel: +91 - 422 - 231 5640 / 41 / 44

🞽 info@penguin.in







Applications:

Coil of hoses / wires / cables, rings, wheels & rolls.